



Fuse-link, high speed, 1000 A, AC 1000 V, 150 kA, size 3, 74 x 92 x 76 mm, aR, IEC, UL, type K indicator

Part no. **FUSE 1000A 1000V 3BKN/75 AR UR**
 Catalog No. **170M8610**

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	1000
Rated voltage			AC 1000 V
Construction size			size 3
Size			74 x 92 x 76 mm
Utilization category			aR
Status indicator			type K indicator
Breaking Capacity		kA	150
usable for size/applications			semiconductor protection
Standard/Approval			IEC UL
Shape			square body with flush end contacts
Standards/Regulations			IEC 60269-4

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])			
Fuse construction type according to IEC 60269			Other
Type of current			
Rated voltage AC		V	1000
Rated voltage DC		V	
Rated current		A	1000
Utilization category			aR (accompanied semiconductor protection)
Breaking capacity		kA	
Colour code			
Type of fuse status indicator			Other
Power loss at rated current		W	150
Mounting holes			
Centre-to-centre distance of connections		mm	

Additional product information (links)

Product datasheet (pdf)	http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/Catalogs/BUS_Ele_SB_Flush_End_Contact_50_1400A.pdf
Product datasheet (web)	http://www.cooperindustries.com/content/public/en/bussmann/electrical/products/high_speed_square_body/square_body_flushendcontact501400a.html